



The intelligent choice











SMART. The intelligent choice

# INTELLIGENT SECURITY FOR YOUR GATE

When it's time to beef up security, you need **real** muscle, the kind that only **the number one in access automation** can deliver. Introducing the brand new **D20 SMART** industrial sliding gate motor. Packing a heavy duty DC motor, this powerhouse can move a gate weighing up to two tonnes like it's nothing. Because the **D20 SMART** has two backup batteries, it gives you uninterrupted security, convenience and peace of mind. With such a rugged design and the toughest exterior, **it's just built that way**.

Complementing its tough-as-nails mechanical build, **SMART** technology makes the **D20 SMART** as intelligent as it's solid. Everything from setting the limits to managing remotes is done wirelessly using the MyCentsys Pro app, which acts as a complete, highly intuitive user interface that also provides diagnostic feedback and monitors system health in real-time.

If your high-volume site calls for the kind of security that never backs down even when it's pushed beyond the limits of other gate motors, make the intelligent choice and get the **D20 SMART.** 





## **MAIN FEATURES**

## Smooth and strong

A lesser operator would move your big gate very grudgingly, resulting in a lot of rattling and wobbling that take a serious toll on your system's longevity. The **D20 SMART's** powerful motor treats even the most massive gates like a featherweight – moving with a silky smoothness that ensures a long and healthy lifespan.

## **Alert and agile**

This mighty motor moves with exceptional grace. Reliable Hall Effect technology keeps track of the gate position at all times, and ensures pin-point stopping. The unit also boasts advanced safety features and cutting-edge obstruction detection technology, ensuring that your gate isn't only secure, but completely safe.

## **Staying power**

The **D20 SMART's** starting and stopping power makes it the best in its class, and the die-cast aluminium gearbox is the very definition of rugged. Being so strong means that the **D20 SMART** will last longer as its parts are never put under any serious stress.

## SMART hardware

Not only is the **D20 SMART** beautifully-styled, but it provides the best experience for installers with easy access to mounting hardware, backward compatibility (drop-in replacement) on existing A10 base plates, optimised cable routing and a dedicated accessory tray for complementary solutions such as GSM modules.

## SMART connectivity

Set the gate limits, speed, automatic closing and unique profiles for everyone using the gate, with just a few taps.



#### **SMART** security

We've designed a custom theft-deterrent bracket for the **D20 SMART** that threads through the gearbox. Additionally, the unit has a built-in vibration sensor that can be linked to an alarm to alert you to movement or tampering at the gate, potentially helping to prevent theft of the gate motor as well as break-ins. You can even link the sensor to your armed response company to ensure swift reaction in the event of these scenarios.

#### **SMART** diagnostics

The MyCentsys Pro mobile app connects wirelessly to our **D20 SMART** gate motor and gives you instant access to advanced, in-app diagnostics and logs, monitoring system health in real time and saving you time and effort.

#### **Operate wirelessly**

The **D20 SMART** can store up to 1500 individual NOVA remote controls – and now, with the new MyCentsys Pro mobile app, managing the remote control database just couldn't be easier. MyCentsys Pro enables you or your installer to quickly and effortlessly add, edit, delete and label remotes as well as setting up each individual button's associated functionality, for example opening a gate fully or for pedestrians, saving you time, allowing you to customise each remote control button to suit individual requirements, and making life easier for everyone. The operator's huge remote memory capacity makes it the right fit for high-volume commercial and industrial sites.

## **ACCESSORIES**





**Steel Rack** Steel rack is available in different lengths to accommodate any gate



**Photon SMART Safety** Beams Fully-wireless infrared beams.

Always recommended on any SMART automated installation



**CENTURION Transmitters** Available in one-, twoand four-button variants. Incorporates code-hopping encryption



Passive sensitive edge provides additional protection against crushing



Theft-Detterant Cage & Padlock Patented design provides excellent deterrence against theft, tampering and vandalism



**Gate Stations** Communication hub for the G-SPEAK ULTRA GSM intercom available in both durable plastic and stylish and strong metal enclosures



Gooseneck Steel pole for mounting intercom gate station or access control reader



12V-24V SMART Siren The ultimate security companion, designed to seamlessly integrate with your existing SMART gate and garage door operators (not shown in diagram)



SMARTGUARD or **SMARTGUARDair Keypad** Cost-effective and versatile wired and wireless keypad, allowing access to users with a customised code



Wheel Kits A variety of wheel kits are available from your CENTURION dealer

15



**FLUX SA Loop Detector** 

Allows free-exit of vehicles from

the property - requires ground

loop to be fitted

**Solar Supply Solution** Alternative means of powering the system - consult your CENTURION dealer



**G-ULTRA** The ultimate GSM solution for monitoring and activating the operator via your mobile phone



**G-SPEAK ULTRA** Answer your intercom from anywhere for maximum security and convenience - powered by 4G technology



**SMART PowerPack** Power unwavering gate performance for busy sites. Run your gate directly from mains. Optional battery backup for added flexibility





6

## **TECHNICAL SPECIFICATIONS**

Technical Data	D20-SMART	
Input voltage	110V - 240V AC @ 50/60Hz	
Current consumption (Mains)	590mA	
Battery charger current output	1.8A@ 27.6V (+/-5%), 52W	
Maximum number of operations per day	750 <b>2.5</b>	
Duty cycle - Mains present <sup>2,3</sup>	45%	
Motor voltage	24V DC	
Motor power supply	Battery-driven (Standard Capacity - 2x 7.2Ah) <sup>3</sup>	
Current consumption (motor at rated load)	9A	
Input / Output sink currents (Max accessory current draw)		
I/O 1-4	100mA (12/24V)	
I/O 5 and 6	3A (12/24V) 10sec Pulse	
Motor push force - starting	52kgf	
Motor push force - rated	39kgf	
Gate mass - maximum	2000kg	
Gate length - maximum	25m	
Gate speed (varies with load) <sup>2,5</sup>	Up to 18m/min <sup>3</sup>	
Manual Override	Lockable lever with key release	
Drive Pinion	13T Module 4	
Operations in standby with 2x 7.2Ah batteries	Operating Mode	
	Power Saving 15m/min 20kgf	Normal 18m/min 20kgf
Half day <sup>2,3,4</sup>	101	55
Full day <sup>2,3,4</sup>	80	45
Collision Sensing	Electronic	
Operating temperature range	-15°C to +50°C	
Onboard receiver type	CENTURION rolling code (Keelog encryption) multichannel	
Receiver code storage capacity	1500 Remotes <sup>6</sup>	
Receiver frequency	433.92MHz	
Degree of protection	IP54	
Mass of unit packed (with standard kit, but excl. rack and battery)	13kg	
Packaging dimensions (with standard kit, but excl. rack and battery)	350mm wide x 282mm deep x 470mm high	
Can operate off a solar supply, consult your local dealer for assistance	5. Can increase battery capacity for longer standby times	
2 Based on 25°C ambient temperature and unit not in direct sunlight	6 Based on Am gate excluding all accessories	

Based on 25°C ambient temperature and unit not in direct sunlight 2.


Based on a motor push force of less than 50% of rated (Starting and Running forces) 3. 4.

Gate opening and closing speeds can be configured to run slower depending on the requirements of individual installations

Based on 4m gate, excluding all accessories 6.

7. Multiple buttons per remote can be used

## **OVERALL DIMENSIONS**





1271.D.02.0002\_04042024

Call 0860-CENTURION (0860 236 887) to order or to find out more WhatsApp Technical Support Line: +27 (0)83 650 4010 (Monday - Friday: 08h00 - 16h30, Saturday 08h00 - 14h00) E&OE. Centurion Systems (Phy) Lid reserves the right to change any product without prior notice