CENTURION



Wi-Fi

D3 SMART+

RESIDENTIAL SLIDING GATE OPERATOR

SMART+

Always On. Always Connected. Always Communicating.

A BRAND OF FAAC TECHNOLOGIES

ISO 9001:2015 · DESIGNED AND BUILT IN SOUTH AFRICA · 24 MONTH WARRANTY · UK CA



Control. Clarity. Confidence.

In reality, fault-finding usually only starts once the installer is on site. Until then, it's difficult to confirm the issue or the exact parts needed, so installers often arrive without a clear diagnosis, wasting time and travel.

SMΔRT+ changes everything

Installers can now configure settings, view device health, live status, logs, and I/Os remotely before a callout. With a secure remote session, installers can verify faults and confirm parts before going to site. Homeowners approve access with a one-time PIN and stay in control throughout. Less wasted time and travel. Faster fixes. The installer arrives on site knowing the issue, with a confirmed solution and the right parts on hand.

Diagnose off-site.

Confirm the fault.

Arrive prepared.

SMΔRT+

A connected ecosystem where installers work smarter, homeowners stay in control, and issues get solved faster.

INSTALLERS

No more wasted trips. No more wasted time.

- Access health, fault logs, and live status in MyCentsys Pro
- Verify the issue remotely before you leave to site
- Arrive better prepared with the right parts on hand
- Protect your workmanship with clear fault history and event logs
- Tie your installer access code to you
- Installer digital business card

END-USERS

Stay informed. Stay in control.

- View activity, battery status, and mains power changes on your phone
- Open, close, and monitor your gate or garage from anywhere
- Share a one-time PIN for time-limited diagnostics
- Stay informed with real-time alerts



WHAT DISTINGUISHES THE D3 SMART+?

The **D3 SMART+** is the most affordable way into the **SMART+** range. It delivers dependable performance during power interruptions, plus remote control, management and clear visibility of your gate through built-in always-on cloud connectivity.

- **Perfect fit for common residential gates:** Suitable for gates weighing up to 300kg and up to 10m in length, which covers the majority of typical residential installations
- **Suitable speed for everyday convenience:** Gate speed up to 24m/min for responsive daily access
- **Nylon pinion advantage:** A quieter, smoother operation
- **Two dedicated inputs:** For safety beams and inductive loops

FEATURES:

- **Gate capability:** Up to 300kg gates
- **24m/min max speed:** 21m/min (rated load)
- **Motor power supply:** 1 x 12V 7Ah battery-driven
- **Connectivity:** Smartphone/app control over 2.4 GHz wireless
- **Receiver capacity:** 1500 remotes
- **Nylon pinion**
- **Two dedicated inputs**

INSTALLERS

Seamless remote support and troubleshooting.

- **Remote support:** Built-in always-on cloud connectivity speeds up fault finding and cuts unnecessary trips to site
- **Pre-dispatch clarity:** Confirm the likely fault and parts before travelling to site, helping create visibility of the situation beforehand

END-USERS

Control what matters. Know what's happening.

- **The D3 SMART+ continues to operate, even during power interruptions:** Battery-driven operation ensures continuity when mains power is unavailable
- **More visibility and control:** Always-on cloud connectivity lets you check your gate status, and control your gate remotely from the MyCentsys Remote app



Three Apps. A Smarter Access Experience.

SMARTER CONTROL. BETTER SUPPORT. GREATER CONVENIENCE.

From installer setup and support to everyday end-user control, our app ecosystem makes compatible SMΔRT+ and SMΔRT gate and garage door operators easier to manage. Each app plays a dedicated role, helping simplify setup, speed up support and make daily access more convenient. Connect over 2.4 GHz wireless for remote* access through the SMΔRT+ ecosystem, with Apple CarPlay and Android Auto integration for convenient control from your vehicle.

MYCENTSYS PRO

For Professional Installers

Set up, configure and support compatible SMΔRT+ and SMΔRT operators from one installer-focused app. MyCentsys Pro provides quick access to key system information, customer support tools, and secure Remote Sessions* authorised by the end-user through the MyCentsys app.

MYCENTSYS

Empowering the End-user

Manage selected SMΔRT+ and SMΔRT operator functions, monitor system activity, and securely authorise Installer Remote Sessions* with a one-time PIN (SMΔRT+ only). MyCentsys gives users greater visibility and control, helping them stay connected*.

MYCENTSYS REMOTE

For Everyday Access Control

Control SMΔRT+ and SMΔRT gate and garage door operators from your smartphone. MyCentsys Remote provides convenient control when you are near your gate or garage and, where connectivity is available, allows remote monitoring and operation from virtually anywhere*.

For SMΔRT operators, this functionality is enabled through a compatible GSM device, while SMΔRT+ operators have it built in.

DOWNLOAD OUR MOBILE APPLICATIONS for a SMΔRT experience

Download on the App Store | Get it on Google play | EXPLORE IT ON AppGallery

Works with Apple CarPlay | Works with Android Auto

*Remote functionality requires an active internet connection

ACCESSORIES





Nylon RAZ or Nylon Angle Rack
A variety of racks available in different lengths, for different strengths



Photon SMART Safety Beams
Fully-wireless infrared beams. Always recommended on any SMART and SMART+ automated installation



P36
Passive sensitive edge provides additional protection against crushing



Gate Stations
Communication hub for the G-SPEAK ULTRA GSM intercom – available in both durable plastic and stylish and strong metal enclosures



SMARTGUARD or SMARTGUARDair Keypad
Cost-effective and versatile wired and wireless keypad, allowing access to users with a customised code



FLUX SA Loop Detector
Allows free-exit of vehicles from the property - requires ground loop to be fitted



CENTURION Transmitters
Available in one-, two- and four-button variants. Incorporates code-hopping encryption



Theft-deterrent Cage & Padlock
Patented design provides excellent deterrence against theft, tampering and vandalism



Gooseneck
Steel pole for mounting intercom gate station or access control reader



Wheel Kits
A variety of wheel kits are available from your CENTURION dealer



Solar Supply Solution
Alternative means of powering the system - consult your CENTURION dealer



G-ULTRA
The ultimate GSM solution for monitoring and activating the operator via your mobile phone



G-SPEAK ULTRA
Answer your intercom from anywhere for maximum security and convenience - powered by 4G technology



Low-Voltage Charger
Enjoy a safe, reliable and cost-effective way to power your gate operator and enjoy outstanding performance and exceptional flexibility

TECHNICAL SPECIFICATIONS

Technical Data	D3 SMART+	
Input voltage[1]	100V - 240V AC 50/60Hz	
Current consumption (Mains)	320mA peak	
DX12V Battery charger current output	1.8A @ 14.3V +/- 5% (28W)	
Maximum number of operations per day[3,6]	20	
Duty cycle - Mains present[2,3]	25%	
Motor voltage	12V DC	
Motor power supply[5]	Battery-driven (Standard Capacity - 1x 12V 7Ah)	
Current consumption (motor at rated load)	11A	
Input / Output sink currents (Max accessory current draw)		
Fuse Protection	Type	Rating
Main Control Card	Serviceable	35A Mini ATO
Aux. Supply	Resetable Fuse	12V 300mA MAX
Charger (Mains Supply)	Non-serviceable	3A slow-blow
Motor push force - starting	18kgf (Maximum)	
Motor push force - rated	12kgf (Maximum)	
Gate mass - maximum	300kg	
Gate length - maximum[8]	10m	
Gate speed (varies with load)[4]	Maximum	Rated
	Up to 24m/min	Up to 21m/min
Manual Override	Lockable with key release	
Operations whilst in battery backup mode (7.2Ah batteries)	24m/min (7kgf)	21m/min (12kgf)
Half day[5,6,8]	90	80
Full day[5,6,8]	70	65
Collision Sensing	Electronic	
Operating temperature range	-15°C to +50°C	
Onboard receiver type	Code-hopping multichannel receiver with selective add and delete	
Connectivity	Smartphone/app control over 2.4 GHz wireless	
Receiver code storage capacity[7]	1500 Remotes	
Receiver frequency	433.92MHz	
Degree of protection	IP55	
Mass of unit packed (with standard kit, but excl. Rack and Battery)	6.7kg	
Packaging dimensions (with standard kit, but excl. Rack and Battery)	325mm wide x 245mm deep x 395mm high	

1. Can operate off a solar supply, consult your local dealer for assistance.
2. Based on 25°C ambient temperature and unit not in direct sunlight.
3. Based on a motor push force of less than 50% of rated (Starting and Running forces).
4. Gate opening and closing speeds can be configured to run slower depending on the requirements of individual installations.
5. Can increase battery capacity for longer standby times.
6. Based on 4m gate, excluding all accessories.
7. Multiple buttons per remote can be used.
8. Dependent on push force.

OVERALL DIMENSIONS



Call: 09 263 6967 (Auckland) or 03 318 1211 (Christchurch) to order or to find out more
Technical Support Email: technical@aero.net.nz
Monday - Friday: 08h00 - 16h00 & Saturday: 08h00 - 14h00
E&OE. Centurion Systems (Pty) Ltd reserves the right to change any product without prior notice.